

M-30i

METAPACE M-30i

Compact mobile printer
for 3" receipts and labels

Technical Specifications

PRINT

Printing method	Direct thermal
Print speed	max. 100mm/sec
Print width	max. 72mm
Resolution	203 x 203 dpi
Sensors	Paper end, cover open

MEDIA

Media type	Thermal paper, linerless (optional)
Width	80mm
Roll diameter	max. 50mm
Media thickness	max. 0.07 +/- 0.005mm

ELECTRONICS

Memory	64mbit SDRAM, 32Mbit FlashROM
Interfaces	USB 2.0 FS vCom, Bluetooth 3.0 + DER
Battery	7.4V Li-ion, 2,600mAh, rechargeable
Barcodes	UPC-A, UPC-E, CODE 39, CODE 93, CODE 128, EAN 8, EAN 13, ITF, Codabar, PDF417, QR, Maxicode
Reliability	50km (receipt roll), 10km (linerless paper)

SOFTWARE

Drivers	Windows, OPOS, JPOS, Linux CUPS
Emulation	ESC / POS

SPECIFICATIONS

Standard	Battery, belt clip, belt holster, battery charger, power cable, receipt roll, bag, CD, quick-start guide, cleaning pen
----------	--

WARRANTY

Period	24 months
--------	-----------

HOUSING

Dimensions (WxHxD)	105 x 58 x 126mm
Weight	incl. battery: 385g (0.85 lbs), incl. MSR 405g (0.9 lbs)
Colour	Black

CONDITIONS

Temperature	Operating: -15°C – 50°C (5°F – 122°F) Storage: -30°C – 70°C (-22°F – 158°F)
Humidity	Operating: 10°C – 80°C RH
Drop resistance	1.8m (6 ft.)
Sealing	IP43 (IP54 with protective bag)

Highlights

- + Top-speed receipt and label printing: 100mm/sec.
- + Everything for an immediate start-up is included in the box
- + 1.8m fall protection, as well as an IP54 rating with the optional protective case
- + Compatible with Android, Windows and Apple devices
- + Comprehensive selection of accessories, from a protective case to a magnetic stripe reader

